



LED Lighting for Hazardous Areas

www.zoneled.co.za

Engineered for Explosive and Hazardous Environments



VLP Linear Luminaire

Ex ec IIC Gc T5, Ex tb IIIC T100°C Db IP65



VLP Linear Luminaire

Ex ec IIC Gc T5, Ex tb IIIC T100°C Db IP65



VLP Linear Luminaire




Model	Power	Length	Luminous Efficacy	Luminous Flux	IP Rating	Ex Marking
ZLVP18-2	18W	600mm	120lm/w*	2160lm	IP65	Ex ec IIC T5 Gc, Ex tb IIIC T100° Db IP65
ZLVP36-4	36W	1200mm		4320lm		
ZLVP46-5	46W	1500mm		5520lm		
Electrical Data			Photometric Data			
Operating Voltage	100 - 277V		Luminous Flux		120lm/w	
Frequency	50Hz		Colour Rendering Index		<80	
Power Factor	0.97		Colour T°K		3000K / 4000K / 5000K	
Efficiency	92%		SDCM		3	
Start-up Time	0.1S		Light Distribution Angle		120°	
THD	15%		Unified Glare Rating		22	
Standards			Temperature & Operating Conditions			
Compliance	SANS (IEC) 60079-0:2019 SANS (IEC) 60079-7:2019 SANS (IEC) 60079-31:2014		Operating Temperature		20 ~ + 70°C	
			Ambient Temperature		-30 ~ +40°C	
			LED Life Span		50 000hrs (L80 B10)	
IP Rating	IP65		Warranty		5 Years	



*

VLP Linear Luminaire



Size & Dimensions		Photometric Data	
ZLVP18-2	600x50x48mm	Weight	1.0 Kg
ZLVP36-4	1200x50x48mm	Weight	1.3Kg
ZLVP46-5	1500x50x48mm	Weight	1.6kg
Conditions of Safe use			
*Isolate elsewhere before opening cover *Do not open when energised or an explosive atmosphere is present. *Static hazards may exist, wipe only with a damp cloth			



info@zoneled.co.za