

Technical Data Sheet:

# GREASEGUARD – LiCa Mo/Gr EP2

ETGMGBL03

## Description

GREASEGUARD – LiCa Mo/Gr EP2 extreme pressure grease is a lithium - calcium thickener formulated grease, to provide excellent lubrication to all metal to metal surfaces where the oil boundary lubrication fails, with solid lubricants to meet a variety of high load and shock applications.

## Application

GREASEGUARD – LiCa Mo/Gr EP2 is designed for use in all mining, agricultural, earth moving and other civils equipment such as

- Horse and trailer articulated 5<sup>th</sup> wheels
- Pins and bushes
- Metal to metal slides
- Industrial and mining slow moving open gears

## Characteristics

PROPERTY	Units	Characteristics
Thickening agent		Lithium - Calcium
NGLI Number	-	2
Cone Penetration @ 25°C	Tenths of a mm	265-295
Dropping Point,	°C	260
Low Temperature Pumpability Lincoln Ventmeter @ 400 psi,	°C	-6
Moly Solids, % concentration Mill Size <5 microns	%	2
Graphite	%	2.0
Tackifier	%	1.5
Rust test	PASS/FAIL	Pass
Colour	-	Black

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.