

Crystal Paints
5 Curban St, Underwood QLD 4119
PH: 07 3341 3566

Automotive paint

- **Tough Polyurethane Base:** Crystal Paints Automotive Paint is a resilient polyurethane-based enamel known for its toughness, providing a durable finish for a variety of automotive surfaces.
- **Versatile Application:** Suitable for Cars, Trucks, Motorcycles, Trailers, Tractors, Implements, Mowers, Machinery, Metal Frames, and more. It can be effortlessly applied by brushing, rolling, or spraying directly onto prepared plastics, metals, and most automotive surfaces.
- **Compatibility:** The high-quality formulation allows painting onto most solid pre-painted surfaces, making it a versatile choice for your automotive projects.
- **Spraying Convenience:** For spray application, thin the paint with Mineral Turpentine by adding 5-10%, ensuring a smooth and spit-free operation. Avoid exceeding 15% Mineral Turpentine to prevent paint degradation if possible.

Preparation:

- **Surface Prep:** Remove oxidation, oils, etc., from surfaces to be painted. Sand the surface with 240-320 grit sandpaper. Perform a small test patch for compatibility before completing the painting.
- **Bare Steel:** Undercoat with Crystal Paints Grey Oxide Zinc Chromate Primer for optimal adhesion.
- **Plastics and Fibreglass:** Light sanding is sufficient for motorcycle plastic fairings, automotive plastics, and fiberglass before applying paint.

Drying and Coating Times:

- Drying time and wait times between coats range from 2-4 hours, depending on weather conditions. Ensure each coat is completely dry before applying additional layers.

Clean Up:

- Use Mineral Turpentine for easy and effective clean-up.

Caution:

- **Avoid Mixing:** Do not mix with other paints, solvents, or additives, as this could affect the performance of the paint.
- **Temperature Consideration:** Do not paint if the temperature is less than 12 degrees Celsius..

Extra Tips for Excellence:

- Allow a day between coats for quicker hardness.
- Lightly sand with 240 grit before each coat for a smooth and glossy finish.

Product Inquiry:

If unsure about any aspect of this product, do not hesitate to contact Crystal Paints Factory directly for expert guidance.