

## Crystal Paints Tile, Laminate & Melamine

### Key Features:

- **Multiple Application Methods:** Brush, roll, or spray – Crystal Paints Tile, Laminate & Melamine Paint accommodates your preferred application technique, providing flexibility for various surfaces, including benchtops, doors, walls, and more.

### Preparation:

- **For Tiles:** Sand tiles with 240 – 320 grit sandpaper, ensuring a thorough cleaning for a perfect surface. Eliminate any shiny tile surfaces. For floors, incorporate anti-slip grit between coats for added safety.
- **For Laminate & Melamine:** Sand with 240 – 320 grit sandpaper and clean meticulously. Non-experienced painters can achieve the best results using a fine bristle brush or a short nap roller like mohair. If spraying, thin the paint with mineral turps for a flawless finish.

### Drying and Recoat:

- Crystal Paints Tile, Laminate & Melamine Paint dries in 2-4 hours, with a recoat time of 2-4 hours depending on weather conditions. For the best results, it is recommended to recoat after 12 to 24 hours to achieve a harder and stronger finish. Full curing time is at least 1-3 weeks.

### Application Tips:

- **Proper Mixing:** Stir the paint well and check for settling at the bottom of the can before applying.
- **Coverage:** 1 litre can cover up to 12 square meters on tiles, with potential for more depending on tile grout.

**Clean Up:** Use Mineral turpentine for easy and effective cleanup. Don't use any cleaning products that leave a residue.

### Cautions and Recommendations:

- **Temperature Consideration:** Avoid painting in temperatures less than 12 degrees Celsius.

### Extra Tips for Excellence:

- **Enhanced Hardness:** Leaving a day between coats accelerates hardness. Lightly sand with 240 grit before each coat for a smooth, glossy finish.

**Product Inquiry:** If unsure about any aspect, contact Crystal Paints Factory directly for expert guidance.