

R-Value Table

Insulation Values For Selected Materials

Use the R-value table below to help you determine the R-value of your wall or ceiling assemblies. To obtain a wall or ceiling assembly R-value you must add the r-values of the individual components together. See the following example:

Wall Assembly R-Value

Component	R-value
Wall - Outside Air Film	0.17
Siding - Wood Bevel	0.80
Plywood Sheathing - 1/2"	0.63
3 1/2" Fiberglass Batt	11.00
1/2" Drywall	0.45
Inside Air Film	0.68
Total Wall Assembly R-Value	15.73

R-Value Table

Material	R/ Inch	R/ Thickness
Insulation Materials		
Fiberglass Batt	3.14	
Fiberglass Blown (attic)	2.20	
Fiberglass Blown (wall)	3.20	
Rock Wool Batt	3.14	
Rock Wool Blown (attic)	3.10	
Rock Wool Blown (wall)	3.03	
Cellulose Blown (attic)	3.13	
Cellulose Blown (wall)	3.70	
Vermiculite	2.13	
Autoclaved Aerated Concrete	3.90	
Urea Terpolymer Foam	4.48	
Rigid Fiberglass (> 4lb/ft3)	4.00	
Expanded Polystyrene (beadboard)	4.00	
Extruded Polystyrene	5.00	
Polyurethane (foamed-in-place)	6.25	
Polyisocyanurate (foil-faced)	7.20	
Construction Materials		
Concrete Block 4"		0.80
Concrete Block 8"		1.11
Concrete Block 12"		1.28
Brick 4" common		0.80
Brick 4" face		0.44

Poured Concrete	0.08	
Soft Wood Lumber	1.25	
2" nominal (1 1/2")		1.88
2x4 (3 1/2")		4.38
2x6 (5 1/2")		6.88
Cedar Logs and Lumber	1.33	
Sheathing Materials		
Plywood	1.25	
1/4"		0.31
3/8"		0.47
1/2"		0.63
5/8"		0.77
3/4"		0.94
Fiberboard	2.64	
1/2"		1.32
25/32"		2.06
Fiberglass (3/4")		3.00
(1")		4.00
(1 1/2")		6.00
Extruded Polystyrene (3/4")		3.75
(1")		5.00
(1 1/2")		7.50
Foil-faced Polyisocyanurate (3/4")		5.40
(1")		7.20
(1 1/2")		10.80
Siding Materials		
Hardboard (1/2")		0.34
Plywood (5/8")		0.77
(3/4")		0.93
Wood Bevel Lapped		0.80
Aluminum, Steel, Vinyl (hollow backed)		0.61
(w/ 1/2" Insulating board)		1.80
Brick 4"		0.44
Interior Finish Materials		
Gypsum Board (drywall 1/2")		0.45
(5/8")		0.56
Paneling (3/8")		0.47
Flooring Materials		
Plywood	1.25	
(3/4")		0.93

Particle Board (underlayment)	1.31	
(5/8")		0.82
Hardwood Flooring	0.91	
(3/4")		0.68
Tile, Linoleum		0.05
Carpet (fibrous pad)		2.08
(rubber pad)		1.23
Roofing Materials		
Asphalt Shingles		0.44
Wood Shingles		0.97
Windows		
Single Glass		0.91
w/storm		2.00
Double insulating glass (3/16") air space		1.61
(1/4" air space)		1.69
(1/2" air space)		2.04
(3/4" air space)		2.38
(1/2" w/ Low-E 0.20)		3.13
(w/ suspended film)		2.77
(w/ 2 suspended films)		3.85
(w/ suspended film and low-E)		4.05
Triple insulating glass (1/4" air spaces)		2.56
(1/2" air spaces)		3.23
Addition for tight fitting drapes or shades, or closed blinds		0.29
Doors		
Wood Hollow Core Flush (1 3/4")		2.17
Solid Core Flush (1 3/4")		3.03
Solid Core Flush (2 1/4")		3.70
Panel Door w/ 7/16" Panels (1 3/4")		1.85
Storm Door (wood 50% glass)		1.25
(metal)		1.00
Metal Insulating (2" w/ urethane)		15.00
Air Films		
Interior Ceiling		0.61
Interior Wall		0.68
Exterior		0.17
Air Spaces		
1/2" to 4" approximately		1.00