



## Tapecoat® M-860

Tapecoat® M-860 is a pre-formed cold-applied, self-adhering material that is impermeable to water and salt. The adhesive is manufactured from specially formulated Elastomeric resins bonded to a woven polymer for high puncture resistance; the rolls have an easy-to-remove plastic release film that protects the adhesive from contamination prior to application.

Tapecoat® M-860 should be applied over dry pavement or concrete that is free of dirt, debris or other foreign matter. Pavement cracks wider than 3/8" should be pre-filled with hot or cold crack material prior to applying Tapecoat M-860 to assure longer protection of the crack filling material against surface wear.

Packaged in cartons as follows:

3 rolls - 4" x 150'

2 rolls- 6" x 150'

1 roll - 12" x 150' Additional widths up to 24" wide available upon request.

PHYSICAL PROPERTIES		
Property	Value	Test Method
Thickness	.065" Nominal	-
Water Vapor Transmission Rate, Permeance	0.01 perms (grains(sq.ft./hr./in. Hg) Maximum	ASTM E-96 Method B
Tensile Strength	50 lb./in Minimum	ASTM D-882 Modified for 1" Opening
Puncture Resistance (Mesh)	200 lb. Minimum	ASTM E-164
Pliability-1/4" Mandrel 180° bend -30°F	No cracks in mesh or adhesive	ASTM D-146



TITUS® Industrial Group, Inc.  
 Toll Free: 877-582-9899 or 541-389-1975  
 Fax: 541-389-2911 Email: [info@titusig.com](mailto:info@titusig.com)  
 Website [www.titusig.com](http://www.titusig.com)