



Builders Choice Collection
[Wood Grain | SPC | 4.5MM]

#1420 WG-RIG, #1421 WG-RIG, #1422 WG-RIG, #1423 WG-RIG
#1424 WG-RIG, #1425 WG-RIG, #1426 WG-RIG, #1427 WG-RIG
#1428 WG-RIG, #1429 WG-RIG, #1430 WG-RIG

SERIES INFORMATION:

Colors:	Thickness	Width	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#1420 WG-RIG-#1430 WG-RIG	4.5MM	7 1/8"	48"	12MIL	28.84	50	1442	44	1.53 lbs	4-6%

INSTALLATION

- Nail
- Nail/Glue Assist
- Glue Only
- Float
- Click
- Below Grade
- Radiant Heat

ADDITIONAL INFORMATION:

Core Construction	Tuffcore SPC (Polyvinyl Chloride)
Core Type	SPC (Virgin) 2000+ PSI
Joint System	I4F Triple Lock
Texture	Wire Brushed
Edge Profile	Pressed Edge .7mm
Finish Type	2 Coats of UV cured urethane infused with ceramic.
Gloss Levels	5 - 7%
Maintenance	ZEP Neutral Floor Cleaner
Repair Finish	Dr. Schutz Scratch Fix - Vinyl Design Floor Repair
Expansion Requirements	1/4" expansion gap for the first 20 Lineal feet (length or width). Add additional 1/16" for every 5' of install (length or width) upto 1/2". T-molds are required for rooms exceeding 50 lineal feet in length and width and 40 lineal feet for installations over in floor radiant heat.

COMPLIANCE:

This series has been tested and contains the following certifications:



LIMITED WARRANTY

Finish: Limited Lifetime
Structural: 10 year Commercial

COMMON QUESTIONS:

SUBSTATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius or 1/8" in 6' radius, vertical deflection cannot exceed 1/4" in 10' Radius, or more than 1/16" between the floor joist.

APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB, 3000 PSI concrete or 2500 PSI gypcrete. Underlayment grade MDF. See installation guide for additional approved substrates.

WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Should not exceed 12% MC (moisture content).

CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Properly install a minimum of 6mil plastic over the entire substrate. Overlap all seams 12" and tape all seams with moisture proof tape.

JOBSITE CONDITION RANGES

RH between 30-60% and room temperature between 60 to 80°F. Post installation temperature range must be within 10 to 142°F.

ACCLIMATION TIMEFRAME

No acclimation is required if the product was stored and/or transported in 60 to 80°F for at least 24 hours prior to installation. Otherwise, it must acclimate for a minimum of 24 hours. Please see installation guide for radiant heat application.

CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

This product has an attached 1mm thick high density EVA cushion. An additional cushion is not compatible.

RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Anchor Grip, Nature's Grip, RugPro, or Super Lock Natural.



Color # 1425 WG-RIG Oak



Color # 1420 WG-RIG Oak



Color # 1426 WG-RIG Oak



Color # 1421 WG-RIG Oak



Color # 1427 WG-RIG Oak



Color # 1422 WG-RIG Oak



Color # 1428 WG-RIG Oak



Color # 1423 WG-RIG Oak



Color # 1429 WG-RIG Oak



Color # 1424 WG-RIG Oak



Color # 1430 WG-RIG Oak