

# flooring2.com CITADEL TILE

# **SPC Luxury Vinyl**

## Durable Waterproof Flooring with Ceramic Bead Finish

## **BENEFITS**

- WATERPROOF
- ECO FRIENDLY
- EASY TO INSTALL
   No acclimation required
   Not affected by sunlight



Transitions not required when installation is less than 5,000 SF 10x more resistant to indentation than standard luxury vinyl products









# floor score certified means:

## **ECO FRIENDLY**

Phthalate free & CARB2 Compliant

#### **COORDINATING TRIM OPTIONS**

(Local Stock)

\*Trim measurements are approximate



#### **Quarter Round**

94.5" x .75" x .75"



#### T Molding

94 .5" x 1.75" x .063"



#### Reducer

94.5" x 1.75" x .375"



#### **End Cap**

94.5" x 1.5" x .375"



#### **Overlap Stair Nose**

94.5" x 2.125" x .75" 1.75" to SN Inside Edge



#### **Flush Stair Nose**

94.5" x 3" x 1" 2.44" to SN Inside Edge

### **CONSTRUCTION**

**UV/PU Ceramic Bead Protective Layer** – Protects Against Scratching, Stains and Fading

Wear Layer - Lifetime Residential Warranty

Film Layer - Beautiful Design & Color

**SPC Core** – 5mm Durable, Dent Resistant, Stable

**Pad Layer** -1mm Antimicrobial Pad Quiets Sound Transmission and Gives Comfort Underfoot

#### **SPECIFICATIONS**

• **Dimensions**: 6mm overall thickness - 12" wide x 24" length

• Packaging: 20.03 Sq. Ft. Per Carton (Valinge 2G locking system)

• Profile: Micro-Beveled Edges - 1mm premium antibacterial attached pad

• Finish: 20 mil UV/Polyurethane Wear Layer with Ceramic Bead

• Warranty: Lifetime Residential – 15 Year Full Commercial

#### **INSTALLATION Quick Facts:**

Hydronic Radiant Heat Approved (81F degrees)

Expansion: ¼" gap perimeter

Transitions not required for installations less than 5,000 SF

Inspect flooring prior to installation

Use floor protection for furniture

\*\* Read complete instructions at flooring2.com before installation\*\*

https://flooring2.com Customer Service: 1.855.404.1651





\*Acclimation: Not required