Trust the grip of the SureNail® strip.

There's a line between a good shingle and a great shingle. It's the nailing line on your shingles. The difference is having SureNail Technology.

Excellent Adhesive Power below the shingle layers laminated.

Outstanding Grip ∘-

The SureNail* strip enhances the already amazing grip of our proprietary Tru-Bond* sealant for exceptional wind resistance of a 130-MPH wind warranty.*



→ Breakthrough Design

Patented SureNail* Technology** is the first and only reinforced nailing zone on the face of the shingle.

"No Guess" Wide Nailing Zone

This tough, engineered woven-fabric strip is embedded in the shingle to create an easy-to-see strong, durable fastener zone.



— Triple Layer Protection^{*+}

A unique "triple layer" of reinforcement occurs when the fabric overlays the two shingle layers, called the common bond area.

→ Double the Common Bond

SureNail features up to a 200% wider common bond area in the nailing zone over standard shingles.



Product Attributes

Warranty Length*

Limited Lifetime** (for as long as you own your home)

Wind Resistance Limited Warranty*



130 MPH

Algae Resistance Limited Warranty*

10 Years

TruPROtection® Non-Prorated Limited Warranty® Period

TruDefinition® Duration® Shingles Product Specifications

Nominal Size	131/4" x 393/8"
	5 ⁵ 8"
Exposure Shingles per Square	64
Bundles per Square	3
Coverage per Square	98.4 sq. ft.

Applicable Standards and Codes

ASTM D228	
ASTM D3018 (Type 1)	101
ASTM D3462	
ASTM D3161 (Class F Wind Resistance)	
ASTM D7158 (Class H Wind Resistance)	40
ASTM E108/UL 790 (Class A Fire Resistant	e)
ICC-ES AC438*	
UL ER2453-01**	

Product Attributes

Warranty Length*

Limited Lifetime** (for as long as you own your home)



Wind Resistance Limited Warranty*

130 MPH

Algae Resistance Limited Warranty*

10 Years

TruPROtection® Non-Prorated Limited Warranty* Period

10 Years

TruDefinition® Duration® Shingles Product Specifications

Nominal Size	13 ¹ / ₄ " x 39 ³ / ₈ "
Exposure	55/8"
Shingles per Square	64
Bundles per Square	3
Coverage per Square	98.4 sq. ft.

Applicable Standards and Codes

ASTM D228	
ASTM D3018 (Type 1)	
ASTM D3462	
ASTM D3161 (Class F Wind Resistance)	
ASTM D7158 (Class H Wind Resistance)	
ASTM E108/UL 790 (Class A Fire Resistance)	
ICC-ES AC438#	
III FR2453-01##	

