



Air Component Solutions

Cloth Back PVC

● White / Black PE Insulation



● Black Rubber Insulation



Key Features:

1. Materials: Copper meets C12200 and ASTM B 280
2. Produce white PE and Black rubber insulation, meets ASTM E84, UL94, ASTM D1056 and ASTM G 21.
3. Suitable usage -40 C - 120 C
4. 1ft-50ft copper line set both of the two copper pipe ends can do flaring and nuts.

Size	Copper pipe	Thickness insulation size	Length available	Flame resistant
1/4+3/8	6.35x0.75+9.52x0.8mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
1/4+1/2	6.35x0.75+12.7x0.8mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
1/4+5/8	6.35x0.75+15.88x0.9mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
3/8+5/8	9.52x0.8+15.88x0.9mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
3/8+3/4	9.52x0.8+19.05x0.9mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
1/2+3/4	12.7x0.8+19.05x0.9mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1
3/8+7/8	9.52x0.8+22.22x1.14mm	3/8"/1/2"/3/4"/1"	1ft - 164ft	M1/B1