



DW 468

Glass Cloth

Product Description

This product is a glass cloth tape with an aggressive silicone adhesive on both sides.

Application Information

This tape is designed for high temperature plasma and flame spray masking. The use of an overlay when grit blasting may be needed. The overlap end is designed not to lift at high velocity grit blasting or thermal spray.

Technical Data	Test Method	Results	Metric Results
Backing Material		Glass Cloth	
Backing Thickness		0.004 in.	0.01 cm
Adhesive System		Silicone	
Adhesive Thickness		0.003 in.	0.008 cm
Adhesion	ASTM - D 1000	30 oz./in.	334.83 g/cm
Tensile Strength	ASTM - D 3759	175 lb./in.	31.252 kg/cm
Max. Operating Temp.		500 °F	260 °C
Rolls-Royce Aero Repair	CSS13	Approved	

Packaging Specifications	English	Metric
Core I.D.	3 in.	7.62 cm
Roll Length	36 yds.	32.92 m
Width	0.25 to 36 in.	0.635 to 91.44 cm

Above are "Typical Values" not intended for specifications. DeWAL requests the opportunity to work with you on specifications.

DeWAL Industries • 15 Ray Trainor Drive, Narragansett, RI 02882
1-800-366-8356 • 001-401-789-9736 • www.dewal.com • usa1@dewal.com

05-21-2013