Project Backboard Court Renovation Process

- 1. Contractor: Power-wash (½-1 day)
- 2. Contractor: Crack fill and patch repair low areas (1-2 days) C
- 3. Contractor: Apply Acrylic Resurfacer (1+ day)
- 4. Draw artwork using a grid or other method
- 5. Paint court art using sports specific color coatings applied with squeegees and wide brushes. (@4-5 days per court)
- 6. Contractor: Paint game lines (1 day)

Court Artwork Considerations/Recommendations

- 1. Due to perspective and scale one should not need to be able to view the entire work to experience its energy
 - 1. For example, we avoid detailed figurative works
 - 2. Fewer, larger shapes can be more successful than lots of small shapes.
- 2. Try to avoid lines that will have the same width as game lines (2")
- 3. Delicate shading will become hard to see over time due to wear and dirt
- 4. Consider not just what the court will look like on Day 1, but also on Day 1000
 - 1. Areas around the hoop and inside the three point line will experience fading first when heavily used (4-5 years)
 - 2. Areas of design near center and sidelines will last longest
 - 3. Light colors show dirt fast.
 - 4. Avoid portraits because faces will be marked/disfigured by wear.
- 5. Avoid large areas of white because
 - 1. White shows wear fast
 - 1. White can have a harsh glare in the sun
 - 1. Game-lines will be white
- 6. Large black areas absorb heat and can get hot.
- 7. Use stock sports color coatings only.
 - 1. Acrytech has a good range of colors.
 - 2. Sport Master Color Plus Fusion can be custom mixed to make a wide range of colors.
 - 3. Other vendors we have used include; World Class Paints, Streetbond, DecoTurf, PlexiPave, Laykold, NovaColor, etc.