ORO 2.5

The ORO 2.5 is a great roaster for a small coffee shop or as a sample roaster and for advanced home roasting. It can roast from 4oz. to 3lb. per roast and up to 4-5 roasts per hour. It has all the features of the big commercial roasters including Double wall SS drum with front and back cast iron plates. It has 2 FUJI digital temperature controls on the panel for quick viewing of both BT & ET. It has the option of a variable drum speed control and precise airflow control via the MDDS (manual damper) system. Laser cut body with glossy powder coated finish in choice of black, red or cream white. Direct-Connect chaff unit for efficiency & reduced footprint. An LED Lamp provides illuminated viewing. Choice of Stainless steel finish and housing colors.

RPPROVES CELLS OF THE PROVES O

SPEC SHEET

0 0 0		
ORO 2.5	GAS	ELECTRIC
Batch Size	4oz-3lb.	4oz-3lb.
Roasting Time	9-14 minutes	9-14 minutes
Production	12-15lb. hour	12-15lb. hour
Heat Source	NG/LPG	electric
Voltage	220V	220V
Wattage	310W	4800W
Drum Motor	25W	25W
Chaff Fan Motor	60W	60W
Cooling Fan Motor	200w	200W
BTU	20,000	
NG PRESSURE	7WC	
LPG PRESSURE	MAX. 16WC	
Gas Consumption	0.2kg/ hr	
Roaster Dimensions	88x71x104CM 35x28x41 in.	88x71x104CM 35x28x41 in.
Roaster Weight	94/132kg 206/291lb	94/132kg 206/291lb

FEATURES

DRUM
AIRFLOW
TEMP. CONTROL
DATA LOGGING
THERMOCOUPLES
WARRANTY
PARTS AVAILABLE
110V CONVERTER

DOUBLE WALL SS DRUM CAST IRON PLATES
MDDS SYSTEM FOR PRECISE AIRFLOW CONTROL
TWO FUJI CONTROLS
BUILT-IN DATA LOGGING OFF FUJI CONTROLS
TWO K-TYPE FOR ET & BT
1 YEAR PARTS & INSTRUCTION
10 YEAR PARTS STOCK GUARANTEE
INCLUDED ON GAS MODELS

THE ORO 2.5 COMES STANDARD WITH THE M4 SYSTEM WITH 4 DEDICATED MOTORS AND TWO EXHAUSTS. IF YOU PREFER JUST ONE EXHAUST WE CAN CUSTOM ORDER THE M3 SERIES WITH ONE EXHAUST AND A SHARED MOTOR FOR COOLING AND EXHAUST.

