

Sch 40 PVC Industrial Pipe*									
Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
002402	1/4"	41.906	500	5000	7.8	780	0.540"	0.364"	.088"
004402	3/8"	56.480	500	5000	10.5	620	0.675"	0.493"	.091"

TYPE I PVC 1120-1220 SCHEDULE 80 PIPE  
Complies with ASTM D 1785 and Product Standard PS 21-70

Sch 80 PVC Industrial Pipe									
Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
001802	1/8"	43.722	500	5000	5.8	1230	0.405"	0.215"	0.095"
002802	1/4"	52.826	500	5000	9.8	1130	0.540"	0.300"	0.119"
004802	3/8"	72.87	500	5000	13.6	915	0.675"	0.423"	0.126"

HI TEMP CPVC SCHEDULE 40 PIPE  
Complies with ASTM D 1784; ASTM F-441; Commercial Standard CS-207-60

Sch 40 CPVC Industrial Pipe*									
Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
C002402	1/4"		500	5000	8.7	780	0.540"	0.364"	.088"
C004402	3/8"		500	5000	11.7	620	0.675"	0.493"	.091"

Sch 80 CPVC Industrial Pipe									
Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
C001802	1/8"	88.08	500	5000	6.3	1230	0.405"	0.215"	0.095"
C002802	1/4"	121.38	500	5000	11.9	1130	0.540"	0.300"	0.119"
C004802	3/8"	169.88	500	5000	16.5	915	0.675"	0.423"	0.126"
C005802	1/2"	196.41	400	4000	24.3	850	0.840"	0.546"	0.147"
C007802	3/4"	269.09	300	3000	32.9	690	1.050"	0.742"	0.154"

20 Ft. Lengths — Plain Ends, Belled Ends Available Sch 40 Not Recommended For Threading  
NOT RECOMMENDED FOR COMPRESSED AIR OR GAS

\* Threading of Schedule 40 pipe not recommended