

ZSPEC[®]

FLOW CONTROL

VALVES AND FITTINGS

OILFIELD | MARINE | INDUSTRIAL | AGRICULTURE

PRODUCT CATALOG



14 13 16

9 12 11 1




ZSPEC® Flow Control – A top-quality valves and fittings supplier serving distributors in the oil field, industrial, marine and agricultural industries.

Based out of Houston, Texas, ZSPEC® supplies top-quality valves and fittings to distributors throughout the United States. We are guided by a singular determination to do whatever it takes to be a reliable supplier for our customers with our ready-to-ship inventory.

You can learn more about our ZSPEC® product offerings in the corresponding product catalogue and at our website, www.zspec.com.

TABLE OF CONTENTS

RESILIENT SEATED BUTTERFLY VALVES	3
HIGH PERFORMANCE BUTTERFLY VALVES	3, 4
GATE VALVES	4
CHECK VALVES	4
BALL VALVES	5-7
FLANGED END BALL VALVES	7
NON-FREEZE TANK VALVES	7
BULL PLUGS	7
SWAGE NIPPLES	7
SEAMLESS NIPPLES	8
NEEDLE VALVES	8
EXPANSION JOINTS	8
SWIVEL JOINTS	8
PUP JOINTS	9
BOLTED SLEEVE COUPLINGS	9
CHOKES	9
CROSSOVERS	10
FLANGED CROSSOVERS & ADAPTERS	10
BULLDOG TANK UNIONS	11
PLUG VALVES	11
HAMMER UNIONS	12
INTREGRAL FITTINGS	13
MANIFOLDS	13
PONY RODS	14
SUCKER RODS	14
777Z HEAVY DUTY FLEXIBLE COUPLINGS	14



RESILIENT SEATED BUTTERFLY VALVES

BW Series Butterfly Valve



Wafer Style w/ Guide Holes,
Long Neck Design
200 PSI NSCWP
Sizes: 2" thru 20"
(larger diameters are available)

BL Series Butterfly Valve



Lug Style Valve,
Long Neck Design
200 PSI NSCWP
Sizes: 2" thru 20"
(larger diameters are available)

RL Series Butterfly Valve



Lug Style Valve,
2-pc Stem Design
200 PSI NSCWP
Sizes: 2" thru 12"

RRW Series Butterfly Valve



Round Wafer Style,
Long Neck Design
200 PSI NSCWP
Sizes: 2" thru 12"

RNW Series w/ Square Stem



Notched Body Wafer Style,
Short Neck Design, Square Stem
200 PSI NSCWP
Sizes: 2" thru 12"

RNW Series Butterfly Valve



Notched Body Wafer Style,
Short Neck Design
200 PSI NSCWP
Sizes: 2" thru 12"

RNW Teflon Series Butterfly Valve



Notched Body Wafer Style,
Short Neck Design
150 PSI NSCWP
Sizes: 2", 3", 4", 6"

Stem Extension for Butterfly Valves



Stem Extensions are available for all
Butterfly Valves. Standard lengths are
2 ft and 4 ft.

RNW6BT Series Butterfly Valve



6 Bolt Notched Body Wafer Style,
Short Neck Design, Square Stem
200 PSI NSCWP
Sizes: 3", 4", 5"

Gear Op for Butterfly Valves



Gear Operators are available for all
butterfly valves.

T Series Threaded End Butterfly Valve



200 PSI NSCWP
Sizes: 2", 3", 4", 6"

Pneumatic Actuators



Direct Mount Pneumatic Actuators are
available for all butterfly valves
2" thru 12".

G Series Grooved End Butterfly Valve



200 PSI NSCWP
Sizes: 2" thru 12"

Handle for Butterfly Valves



All butterfly valves come standard with
handles, however spare handles may be
purchased.
*They are available for DD and Square stemmed
valves.*

HIGH PERFORMANCE BUTTERFLY VALVES

HP Series High Performance Butterfly Valve



Lug Style valve, CF8M Body and Disc
Classes: 150, 300
Sizes: 3" thru 24"

BGV Series Brass Gate Valve



FNPT Ends
200 PSI NSCPW
Sizes: 3/8" thru 4"

QL Series Quick Lever Brass Gate Valve



FNPT Ends
Sizes: 2", 3", 4", 6"

CHECK VALVES

BCV Series 200 PSI Brass Check Valve



FNPT Ends,
200 PSI NSCPW
Sizes: 3/8" thru 4"

BCVR Series 300 PSI Brass O Ring Style



FNPT Ends, Clapper O-ring
300 PSI NSCPW
Sizes: 1", 2", 3", 4"

BCVRG Series 300 PSI Grooved End Brass O Ring Style Check Valve



Grooved Ends, Clapper O Ring
300 PSI NSCPW
Sizes: 2", 3", 4"

D Series Ductile Iron Swing Check Valve



NACE MR0175, FNPT Ends
Available Pressures: 300, 600, 1,000,
1,500, 2,000 & 2,160 PSI NSCPW
Sizes: 1", 2", 2-1/2", 3", 4"

C Series WCB Swing Check Valve



NACE MR0175, FNPT Ends
3,000 & 5,000 PSI NSCPW
Sizes: 1", 2", 3"

ICV Series 316SS Inline Check Valve



MNPT x FNPT or FNPT x FNPT Ends
Viton O Ring
6,000 or 10,000 PSI NSCPW
Sizes: 1/8", 1/4", 1/2", 3/4", 1"

1000# CF8M Swing Check Valve



1000# CF8M Swing Check Valve
FNPT Ends
1,000 PSI NSCPW
Sizes: 1/2" thru 2"

ICV Series Brass Inline Check Valve



MNPT x FNPT Ends
Viton O Ring
3,000 PSI NSCPW
Sizes: 1/8", 1/4", 1/2", 3/4", 1"

Ductile Iron Ball Type Check Valve



NACE MR0175
FNPT Ends
Viton Seat, 316SS Ball
2,000 PSI NSCPW
Sizes: 1", 2"

CF8M Ball Type Check Valve



NACE MR0175
FNPT Ends
Viton Seat, 316SS Ball
2,000, 3,000 & 5000 PSI NSCPW
Sizes: 1", 2"

WCB Ball Type Check Valve



NACE MR0175
FNPT Ends
Viton Seat, 316SS Ball
2,000, 3,000 & 5000 PSI NSCPW
Sizes: 1", 2"

BALL VALVES

BBV Series Brass Ball Valve



Full Port,
FNPT Ends,
Locking Device Handle
600 PSI NSCW
Sizes: 1/4" thru 4"

BBVH Series Heavy Duty Brass Ball Valve



Heavy Weight Body, Full Port,
FNPT Ends,
Locking Device Handle
600 PSI NWCWP
Sizes: 1", 2", 2-1/2", 3", 4"

1000 Series Oilfield Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
1,000 PSI NSCW
Sizes: 1" FP, 2" RP, 2" FP, 3" RP,
3" FP, 4" RP

1500 Series Oilfield Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
1,500 PSI NSCW
Sizes: 1" FP, 2" RP

2000 Series Oilfield Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
2000 PSI NSCW
Sizes: 1" FP, 2" RP, 2" FP, 2-1/2" FP,
3" RP, 3" FP, 4" RP, 4" FP

3000 Series Oilfield Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
3000 PSI NSCW
Sizes: 1" FP, 2" RP, 2" FP, 2-1/2" FP,
3" FP, 4" FP

3600 Series Oilfield Ball Valve



NACE MR0175,
EUE 8Rnd Ends,
Locking Device Handle
3,600 PSI NSCW
Sizes: 2-3/8, 2-7/8

5000 Series Oilfield Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
5,000 PSI NSCW
Sizes: 1" FP, 2" RP, 2" FP, 2-1/2" FP, 3" FP

1000 Series Non-Freeze Ball Valve



NACE MR0175,
FNPT Ends,
Reduced Port
1,000 PSI NSCW
Sizes: 2", 3", 4"

1500 Series Bolted Body Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
1,500 PSI NSCW
Sizes: 2.5" FP

2000 Series Bolted Body Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
2,000 PSI NSCW
Sizes: 1" FP, 2" FP

3000 Series Bolted Body Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
3,000 PSI NSCW
Sizes: 2" FP

BS2K Series Barstock Ball Valve



NACE MR0175, B16.34 Design,
FNPT Ends,
Standard Non Locking Handle
2,000 PSI NSCW
Sizes: 1/4" thru 2"

5000 Series Bolted Body Ball Valve



NACE MR0175,
FNPT Ends,
Locking Device Handle
5,000 PSI NSCW
Sizes: 2" FP, 2" RP, 3" FP, 4" FP

CS2K Series Seal Welded WCB Ball Valve



NACE MR0175, Full Port,
FNPT Ends,
Locking Device Handle
2,000 PSI NSCW
Sizes: 1/4" thru 2"

BS2K-L Series Barstock Ball Valve



NACE MR0175, B16.34 Design,
FNPT Ends,
Locking Device Handle
2,000 PSI NSCW
Sizes: 1/4" thru 2"

CS1K Series Seal Welded WCB Ball Valve



NACE MR0175, Full Port,
FNPT Ends,
Locking Device Handle
1,000 PSI NSCWP
Sizes: 2-1/2", 3", 4"

CS6K Series WCB Seal Welded Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Full Port up to 1-1/2" size,
FNPT Ends,
Locking Device Handle
6,000 PSI NSCWP
Sizes: 1/4" thru 2"

CS3K Series WCB Seal Welded Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Full Port, FNPT Ends,
Locking Device Handle
3,000 PSI NSCWP
Sizes: 1/4" thru 2"

SS2K Series Seal Welded CF8M Ball Valve



NACE MR0175, Full Port,
FNPT Ends,
Locking Device Handle
2,000 PSI NSCWP
Sizes: 1/4" thru 4"

SS1K Series Seal Welded CF8M Ball Valve



NACE MR0175, Full Port,
FNPT Ends,
Locking Device Handle
1,000 PSI NSCWP
Sizes: 2-1/2", 3", 4"

BVT Series CF8M Bolted Body Ball Valve



NACE MR0175, Full Port
FNPT Ends,
Locking Device Handle
3,000 PSI NSCWP
Sizes: 1", 2"

SSR1K Series Reduced Port CF8M Ball Valve



Reduced Port,
FNPT Ends,
Locking Device Handle
1,000 PSI NSCWP
Sizes: 1/4" thru 2"

SS2K Series Seal Welded CF8M (MXF)



NACE MR0175, Full Port,
MNPT X FNPT Ends
Locking Device Handle
2,000 PSI NSCWP
Sizes: 1/4", 1/2"

CS3K Series WCB Seal Welded Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Full Port, FNPT Ends,
Locking Device Handle
3,000 PSI NSCWP
Sizes: 1/4" thru 2"

BVICS Series WCB Isolator Ball Valve



NACE MR0175,
Full Port,
Locking Device Handles
1" : 2,000 PSI NSCWP
2" : 1,500 PSI NSCWP

SS6K Series CF8M Seal Welded Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Full Port up to 1-1/2" size,
FNPT Ends,
Locking Device Handle
6,000 PSI NSCWP
Sizes: 1/4" thru 2"

GVB Series Grooved End Ball Valve



NACE MR0175,
Grooved Ends, Reduced Port
1,000 PSI NSCWP 2" thru 4"
1,500 PSI NSCWP 6"
Sizes: 2", 3", 4", 6"

BVISS Series CF8M Isolator Ball Valve



NACE MR0175, Full Port,
Locking Device Handles
1": 2,000 PSI NSCWP
2": 1,500 PSI NSCWP

SR Series CF8M Spring Return Handle Type



NACE MR0175,
FNPT Ends, Full Port
2,000 PSI NSCWP
Sizes: 1/2" thru 2"

SR Series WCB Spring Return Handle Type



NACE MR0175,
FNPT Ends, Full Port
2,000 PSI NSCWP
Sizes: 1/2" thru 2"

BVZ Series Socket Weld Ball Valve



NACE MR0175, Firesafe to API607,
Full Port, Socket Weld Ends,
3,000 PSI NSCWP
Sizes: 1/2" thru 2"

BALL VALVES

BVZ Series Threaded Ball Valve



NACE MR0175, Firesafe to API607,
Full Port, FNPT Ends,

FLANGED END BALL VALVES

WCB Flanged End Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Raised Face
Full Port and Reduced Port
Classes: 150, 300, 600
Sizes: 2" thru 6"

CF8M Flanged End Ball Valve



NACE MR0175, Firesafe to API607,
B16.34, Raised Face
Full Port and Reduced Port
Classes: 150, 300, 600
Sizes: 2" thru 6"

NON-FREEZE TANK VALVES

Non-Freeze Tank Valve



150 PSI NSCPW
Sizes: 2", 3"

BULL PLUGS

A234 Bull Plugs



Sizes: 1/8" thru 8"
STD, XH, XXH

SWAGE NIPPLES

A234WPB Swage Nipples



Diameters: 2" thru 10"
STD, XH, XXH

Bevel x Thread A106B Swage Nipples



Diameters: 2" thru 6"
STD, XH

SEAMLESS NIPPLES

S40, S80 and XXH A106 Seamless Nipple



Diameters: 1/4" thru 6"
Lengths: CL thru 12"

S80 316SS Seamless Nipples



Diameters: 1/4" thru 4"
Lengths: CL thru 12"

NEEDLE VALVES

NV Series Needle Valve



Types: Standard or Mini
FNPT x FNPT or MNPT x FNPT
6,000 PSI NSCWP or
10,000 PSI NSCWP
Materials: A105 or 316SS
Sizes: 1/4", 1/2", 3/4", 1"

A Series Angle Needle Valve



NACE MR0175
MNPT x FNPT
6,000 or 10,000 PSI NSCWP
Materials: A105 or 316SS
Sizes: 1/4", 1/2"

R Series Reducing Needle Valve



NACE MR0175
1/2" MNPT x 1/4" FNPT
Pressure: 6,000 PSI NSCWP
Material: 316SS

M Series Multiport Gage Needle Valve



NACE MR0175
MNPT x FNPT
10,000 PSI NSCWP
Material: 316SS
Size: 1/2"

EXPANSION JOINTS

Style 101 150# Expansion Joint



Nitrile with Neoprene Cover
225 PSI NSCWP
Sizes: 2" thru 12"

SWIVEL JOINTS

Code Silver Swivel Joints



FNPT Ends, Figure 602
6,000 PSI NSCWP
Sizes: 1", 1-1/4", 1-1/2", 2", 3"
Styles: 10, 20, 30, 50

Code Silver Swivel Joint Repair Kit



Each kit repairs one turn.
Includes all parts including
the grease fitting.
Sizes: 1", 1-1/4", 1-1/2", 2", 3"

Code Red Swivel Joints



1502 Ends, Long Radius
15,000 PSI NSCWP
1502 Male x Female
1502 Male x Male
Sizes: 2", 3"
Styles: 10, 50

Code Red Swivel Joint Repair Kit



Sizes: 2", 3"

PUP JOINTS

1502 NPS Pup Joints



15,000 PSI NSCWP
Size: 2"
Lengths from 6" up to 20 ft.

BOLTED SLEEVE COUPLINGS

Bolted Sleeve Coupling



Diameters: 1" thru 16"
Lengths: 5", 7", 12", 16", 24"

Spare Parts for Bolted Sleeve Couplings



Bolts: 5/8 x 8, 5/8 x 11, 5/8 x 15,
5/8 x 19, 5/8 x 27
Gaskets: 1" thru 16" available in
Nitrile Rubber

CHOKES

1502 Adjustable Choke



15,000 PSI NSCWP
Size: 2"

ZN60 Adjustable Choke



5,000 PSI NSCWP
Size: 2"
Trims: 3/4" or 1"
Trim Materials: Hardened Steel
or SS + Tungsten Carbide

ZN60 Positive Choke



5,000 PSI NSCWP
Size: 2"

ZN62 Adjustable Choke



5,000 PSI NSCWP
Size: 2-1/16"
Trims: 3/4" or 1"
Trim Materials: Hardened Steel
or SS + Tungsten Carbide

Z63 Adjustable Choke



3,000 PSI NSCWP
Size: 3"
Trim: 2"
Trim Materials: Hardened Steel
or SS + Tungsten Carbide

Z65 Adjustable Choke



5,000 PSI NSCWP
Size: 3"
Trim: 2"
Trim Materials: Hardened Steel
or SS + Tungsten Carbide

1502 Female x Male EUE Crossover



1502 Female x 2-3/8 Male EUE or 1502 Female x 2-7/8 EUE
10,000 PSI NSCWP
Sizes: 2"

1502 Female x Female Crossover



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Female x MNPT Crossover



10,000 PSI NSCWP
Sizes: 2"

1502 Male x Male EUE Crossover



1502 Male x 2-3/8 Male EUE or 1502 Male x 2-7/8 EUE
10,000 PSI NSCWP
Size: 2"

2" 1502 Female x 3 1/2" EUE Crossover

1502 Male x Male Crossover



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Male x Female Crossover



15,000 PSI NSCWP
Sizes: 2", 3"

3" 1502 Female x 2" 1502 Male Crossover



15,000 PSI NSCWP

1502 Male x MNPT Crossover



10,000 PSI NSCWP
Size: 2"

4" Fig 200 Fem x 150 Pattern Flange Crossover



Available in 3" and 5-1/8" Face to Face Dimensions

3" 1502 Male x 2" 1502 Female Crossover



15,000 PSI NSCWP

Flange Adapter Assembly



4" FIG. 200 2-PC Nut
4" FIG. 206 Male x 150 Pattern Flange Adapter
4" Plug (handle type)
Chain Assembly

FLANGE CROSSOVER & ADAPTERS

Female Flange Crossover



1-13/16" 10K X 2" 1502 Female
2-1/16" 10K X 2" 1502 Female
2-1/16" 5K X 2" 1502 Female
2-9/16" 10K x 2" 1502 Female
3-1/8 5K X 2" 1502 Female

Male Flange Crossover

2-1/16" 10K X 2" 1502 Male
2-1/16" 5K X 2" 1502 Male
2-9/16" 10K X 2" 1502 Male

Female Flange Adapters



4" Fig. 200 Female X 125 Pattern Flange
4" Fig. 200 Female X 150 Pattern Flange
4" Fig. 200 Female X 150 Pattern Flange - Long Pattern
6" Fig. 200 Female X 150 Pattern Flange

Male Flange Adapters

1-13/16" 10K X 2" 1502 Female
2-1/16" 10K X 2" 1502 Female
2-1/16" 5K X 2" 1502 Female
2-9/16" 10K x 2" 1502 Female
3-1/8 5K X 2" 1502 Female



BULLDOG TANK UNIONS

ZSPEC® is an authorized distributor of Bulldog Tank Unions

Air Grip Unions

Sizes: 4" thru 16"



Frac Tank Unions

Sizes: 6", 8"
Male Socket Weld Sub with Nut



Mud Tank Unions

Sizes: 3" thru 16"



Frac Plug

Sizes: 6", 8"



Frac Nipple

Sizes: 6", 8"



PLUG VALVES



ZSPEC® plug valves and parts are interchangeable with major brands of LT style plug valves. The valves and the replaceable components (plug, inserts, seal kits) have been engineered for maximum durability and usability.

STANDARD SERVICE

SIZE	PART #	END CONNECTION	NSCWP	END TO END DIMENSION
1 X 1	ZH0028	1502	15000 psi	10.56"
1 X 2	ZH0023	1502	15000 psi	10.56"
2 X 2	ZH0006	1502	15000 psi	13.88"
2 X 2	ZH0032	FNPT	10000 psi	9.50"
3 X 3	ZH0055	1502	15000 psi	17.00"
3 X 3 with Gear Operator	ZH0055G	1502	15000 psi	17.00"

H2S SERVICE

SIZE	PART #	END CONNECTION	NSCWP	END TO END DIMENSION
1 X 2	ZH0118	1502	10000 PSI	10.56"
2 X 2	ZH0109	1502	10000 PSI	13.88"
3 X 3	ZH0016	1502	10000 PSI	17.00"
3 X 3 W/ Gear Operator	ZH0016G	1502	10000 PSI	17.00"



Plug Valve Repair Kit

Zspec® plug valve repair kits include plug, seals & inserts.
Sizes: 1", 2", 3"

HAMMER UNIONS



ZSPEC[®] Hammer Unions are manufactured from high quality forgings and castings. The figure appropriate materials are selected for each respective figure number. Threaded and Butt Weld end connections are both readily available. Material traceability and MTRS are available on all hammer unions.

Figure No.	Color Code	NON-SHOCK COLD WORKING PRESSURE RATING (PSI)		Nominal Pipe Size (in inches)													
		STANDARD SERVICE															
		NSCWP	TEST	.5"	1"	1.25"	1.5"	2"	2.5"	3"	4"	5"	6"	8"	10"	12"	
100	Yellow/Black	1000	1500					●	●	●	●	●	●	●			
110	Burnt Orange/Burnt Orange	2500	3750					●									
110	Brown/Brown	4000	6000					●		●							
200	Gray/Blue	2000	3000		●	●	●	●	●	●	●		●	●	●		
201	Gray/Beige	3000	4000					●	●								
206	Gray/Blue	2000	3000		●	●	●	●	●	●	●		●	●	●		
206H	Gray/Blue	400	600								●						
207	Gray/Blue	2000	3000					●		●	●		●				
211	Blue/Gray	2000	3000					●		●							
300	Light Orange/Gray	2000	3000	●	●			●									
301	Gray/Gray	3000	4500		●			●									
OCT	Gray/Gray	3000	4500		●			●									
400	Maroon/Black	4000	6000					●		●	●					◆	
402	Black/Black	4000	6000					●									
G	Silver/Orange	6000	9000				●	●									
602	Orange/Black	6000	9000		●		●	●	●	●	●						
1002	Blue/Red	10000	15000		●		●	●		●	●	◆	◆				
1003	Green/Black	7500	11250							●	●	●					
1502	Red/Blue	15000	22500		●		●	●	●	●	●	●					

◆ indicates a reduction in working pressure as listed: 12" Fig 400: NSCWP = 2500 psi (3750 psi test)
5" Fig 1002 Threaded: NSCWP = 5000psi (7500 psi test)

5" Fig 1002 Butt Weld: NSCWP = 7500 psi (11250 psi test)
6" Fig 1002 Butt Weld: NSCWP = 7500 psi (11250 psi test)

WARNINGS ON HAMMER UNIONS AND PRODUCTS THAT HAVE HAMMER UNION END CONNECTIONS

When installing and handling any pressure containing products, personnel must be qualified and properly trained on the safe installation and use of the products. Our products are designed and qualified to meet industry standards and it is the user's responsibility in making the appropriate selection of products through any required design and/or analysis of the user's requirements so that the products will not pose any health or safety hazards. Failure to adhere to the warnings listed on this form may result in personal injury or death.

Never strike, impact, tighten or loosen pressurized unions or connections.

Complete and proper make-up of union components is required to attain rated working pressure. Always pay

special attention during the make-up process to ensure that this is achieved.

Never use products that have been damaged or deteriorated or corroded.

Never exceed the rated working pressure of the union or connection.

Never assemble union components that are not identical in size, figure and pressure rating.

Should leakage be detected, take the appropriate steps to assure that the piping system is completely depressurized and any remaining fluid is removed and properly disposed of, then proceed to remove the affected component(s) from service and permanently dispose of the affected component(s).

For overhead installations, follow safe practices with consideration of the combined weight of all components, piping and contained fluids when sizing the piping supports and/or other necessary infrastructure to support the combined weight.

Standard hammer unions and connections are not prepped for sour gas service. Do not interchange standard and sour gas components. Hammer unions and connections prepped for sour gas service will be marked with "Sour Gas Svc." or "H2S".

When temperatures are below 32F, please use extreme caution when making or breaking union connections as the lower temperatures negatively affect the impact strength of iron and steel.

INTEGRAL FITTINGS

1502 Cross FMMM



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Cross FFMM



15,000 PSI NSCWP
Size: 2"

Cushion Elbow FxM



15,000 PSI NSCWP
Sizes: 2", 3"

Cushion Elbow MxM



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Tee FMF



15,000 PSI NSCWP
Size: 2"

1502 Tee MFM



15,000 PSI NSCWP
Size: 2"

1502 Tee FFF



15,000 PSI NSCWP
Size: 2"

1502 Cross MFMF



15,000 PSI NSCWP
Sizes: 2"

Cushion Elbow FxF



15,000 PSI NSCWP
Size: 2"

Double Cushion Elbow FxM



15,000 PSI NSCWP
Size: 2"

1502 Tee FFM



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Tee FMM



15,000 PSI NSCWP
Sizes: 2", 3"

1502 Tee MMM



15,000 PSI NSCWP
Size: 2"

1502 MXF 9.19" Spacer



15,000 PSI NSCWP
Size: 2"

1502 MXF 14" Spacer



15,000 PSI NSCWP
Size: 2"

MANIFOLDS

5 Valve Dual Adjustable Choke Manifold



2x2 1502 Plug Valves with dual 1502 adjustable chokes. Skid Mounted

5 Valve Single Adjustable Choke Manifold



2x2 1502 Plug Valves with single 1502 adjustable chokes. Skid Mounted

Pony Rods



API 11B Grade D AISI 4130
Sizes: 5/8", 3/4", 7/8", 1"
Lengths: 2', 4', 6', 8'

SUCKER ROD COUPLINGS

Sucker Rod Couplings




API 11B Grade D AISI 5140
Class T, Spray Metal & Combination Couplings
Full Size & Slim Hole
Sizes: 5/8", 3/4", 7/8", 1"

777Z HEAVY DUTY FLEXIBLE COUPLINGS

777Z Heavy Duty Flexible Couplings



Sizes: 1" thru 16"



Phone: (713) 329-5700 | Fax: (713) 329-5703 | 7100 Business Park Drive, Suite 180 Houston, TX 77041

www.zspec.com

Our product info, design or construction may change without prior notice.